

DeckWright Technical

Providing sustainable, reassuring performance

Pendulum Test Value

PTV	Slip Risk
00 - 24	High
25 - 35	Moderate
36 to 65	Low
65+	Extremely Low

Durability

We use bauxite aggregate for our anti-slip inserts paired with a specialist liquid resin, precision injected into the groove of the timber deck board. The bauxite aggregate achieves an impressive value of 1.1 Mohs hardness scale.

Durability of the timber boards are species specific, please contact your sales rep for more information.

Packaging & Storage

We provide all of our boards in pallets which are weather wrapped and strapped for security. All packaging from DeckWright is designed to eliminate and risk of sagging, we strongly recommend packaging is withheld until use unless stored in a similar fashion.

Post Installation Treatments

DeckWright boards or boards with our anti-slip treatment can be stained with paints, stains or oils if required. These treatments will not have an adverse effect on the anti-slip.

We do recommend that liquids other than natural liquids that come into contact with the boards are cleaned from the surface of the boards immediately in order to maintain the full effect of the anti-slip treatment and remove unwanted staining of the timber.

After Care & Maintenance

DeckWright boards are a low-maintenance product. We would recommend that boards are maintained with a ad-hoc schedule of sweeping and water pressure washing with 120 bar of pressure at 30cm distance from the boards.

Profile & Length Sizes

Profile

DeckWright supply boards at a standard profile size, nominal **32mmx125mm**. We're capable of supplying custom profile lengths and can anti-slip treat any hardwoods or softwood timbers.

Lengths

DeckWright standard boards come in either 3.6m or 4.8m. We offer other lengths where required, please speak to your sales rep for more information.

15 Year Warranty

DeckWright anti-slip comes with a 15 year warranty.

Treatment Colour

DeckWright anti-slip boards come with either use class 3 treatment or use class 4 treatment depending on end use specification. This gives a slight green colour to the timber which naturally fades into a silver.

Installation

We recommend that installers of our DeckWright anti-slip products follow Timber Decking & Cladding Association guidelines. Please visit: www.tdca.org.uk for more information.

For cutting the boards, please be aware of the strength of the aggregate & resin solution and use an appropriate blade for the job.

Treating areas that have been cut, drilled or notches in the timber boards is strongly recommended to the keep the integrity of the timber.

Disposal

DeckWright boards are non-hazardous materials and can be disposed. Shavings and sawdust bi-products should not be re-used in anyway including but not limited to animal beddings and fires.

For further information, please speak to our team.

info@deckwright.co.uk

01377 796001

www.wj-group.co.uk